

TDS – Kerawax 1301

Information

Product Description

Kerawax 1301 is a fully refined paraffin wax blend, it is suitable for a wide variety of applications.

Physical Properties

Test	Method	Specification	Typical Value
Congealing Point	ASTM D938	64 – 66	65°C
Viscosity @ 100°C,	ASTM D445	5.0 – 7.0	6.5 cSt
Penetration @ 25°C,	BS 1426	9 – 20	13 dmm
Colour, Saybolt	ASTM D156	25 Minimum	30

Statement

- Formulated from materials whose refining history is fully traceable.
- Does not contain or come into contact with any animal or GMO products at any stage of its manufacture.
- Does not contain residual solvents as per guidelines CPMP/ICH283/95.
- Has not been tested on animals by ourselves or on our behalf.
- Kerawax 1301 fits within the definition of: FCM Substance No. 93 Reference No. 95859 Contained in COMMISSION REGULATION No 10/2011



Gavin Ithell – Technical Manager

The information and recommendations in this publication are, to the best of our knowledge, reliable. Users must make their own tests to determine the suitability of these products for their own particular purposes. The company makes no warranty of any kind, expressed or implied, including those of merchantability or fitness for a particular purpose, other than that the material conforms to its applicable current Standard Specifications.