

TDS – Keratech 68

Information

Product Description

A highly refined medicinal grade white oil

Physical Properties

Test	Method	Specification	Typical
Viscosity @ 40°C, cSt,	ASTM D445	65 - 75	70
Viscosity @ 100°C, cSt	ASTM D445		9.5
Colour, Saybolt,	ASTM D156	+25 Minimum	+30
Flash Point, °C,	ASTM D92	200 min	250
Density @ 15°C kg/l	ASTM D4052		0.866
Pour Point, °C	ASTM D5950	-9 Max	-15
Refractive Index @ 25°C	ASTM D1218	1.472 – 1.480	1.474

Statement

- Formulated from materials whose refining history is fully traceable.
- Does not contain or come into contact with any animal or GMO products at any stage of its manufacture.
- Does not contain residual solvents as per guidelines CPMP/ICH283/95.
- Has not been tested on animals by ourselves or on our behalf.
- This product complies with the requirements of the current European Pharmacopoeia as well as FDA 178.3620 (a) and 172.878 Mineral Oil specifications. Mineral oils complying with FDA 21 CFR 178.3620 are allowed for use in many food related applications, as well as for direct food use (regulated in 178.878, e.g. lubricants for bakery plates, coating on fruits etc.).

The information and recommendations in this publication are, to the best of our knowledge, reliable. Users must make their own tests to determine the suitability of these products for their own particular purposes. The company makes no warranty of any kind, expressed or implied, including those of merchantability or fitness for a particular purpose, other than that the material conforms to its applicable current Standard Specifications.